

Conspro Corp.  
Road 175 Km. 0.2 Rio Cañas  
Industrial Park Lot #35  
Caguas, PR 00725  
Tel: 787-653-4900  
Fax: 787-653-4949  
email: info@conspro.com  
www.bullbond.com



# Technical Data Sheet

## CONTACT CEMENT MULTI-USE

### CONSTRUCTION GRADE CONTACT ADHESIVE RED CHLOROPRENE BASED HIGH SOLIDS FORMULA

#### PART 1: GENERAL INFORMATION

##### 1.1 PRODUCT DESCRIPTION

An advanced, high yield, red colored, multi-use contact adhesive based on polychloroprene specially designed for the instant, permanent and water resistant bonding of plastic laminate, plastic veneers, metals, wood, leather, linoleum, vinyl tile, rubber, cork, polyurethane foam, paper and cardboard to wood, concrete, masonry, metal and other porous and non-porous materials.

##### 1.2 BASIC USES:

- Instant Bonding of Plastic Decorative Laminate and Veneers:

- Wood
- Fabrics,
- Paneling
- Leather
- PVC Plastic
- Rubber
- Paper

Cardboard and Other Materials to:

- Wood
- Particle Board
- Plywood
- Metal
- Concrete
- Masonry and similar surfaces

- Instant Bonding of Plastic Vinyl Components to Concrete
- Stucco
- Masonry

#### PART 2: TECHNICAL DATA

##### 2.2 COVERAGE:

APPLICATION RATE AND YIELD	
BULL-BOND® CONTACT CEMENT	
APPLICATION	RATE
Roller	100-200 ft <sup>2</sup> /gallon
Brush	75-100 ft <sup>2</sup> /gallon

#### PART 3: INSTRUCTIONS

##### 3.1 APPLICATION

1. Read product Safety Data Sheet (SDS) and the label safety precautions

BULL-BOND® CONTACT CEMENT MULTI-USE

before use.

2. Turn off all potential ignition sources, stop metal welding (sparks) and extinguish all flames. Keep product and vapors away from heat, open flames and sparks. Do not smoke, eat or drink when using product. Use only in well ventilated areas. Use required safety and personal protection equipment.
3. It is mandatory to stir the product thoroughly for a few minutes before use.
4. Surfaces to be bonded must be clean, dry, and free of oil, grease, waxes, dirt and release agents.
5. Apply an even and uniform coat of the adhesive to both surfaces using brush, roller or spray. Keep parts separated until product dries. Drying time is normally between 20-30 minutes.
6. As soon as adhesive has dried, bonding should proceed. Avoid excessive drying times. Align parts properly and join both surfaces pressing firmly and evenly with hands, rubber mallet, roller or other suitable tools until a good bond is obtained.
7. Product coverage will be approximately 100-200 square feet per gallon subject to the porosity of the bonded materials.
8. Keep container closed when not in use to maintain adhesive in good conditions.
9. Do not cut, weld or reuse empty containers. Empty containers may retain hazardous residuals.
10. Do not sell this product to minors. For professional and industrial use only.

##### 3.2 CURING

Drying time is normally between 20-30 minutes.

##### 3.3 CLEANUP

Clean tool and residues with solvents.

#### PART 4: PRECAUTIONS

##### DANGER

##### 4.1 Hazard Statements

Highly Flammable liquid and vapor. Causes eye and skin irritation. May causes drowsiness or dizziness. May causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

##### 4.2 Precautionary Statement

Wear protective gloves / protective clothing / eye protection / face protection. Wash hands thoroughly after handling. Avoid breathing fumes / gas / mist / vapor /spray. Use only outdoors or in well-ventilated area.  
- If swallowed: Immediately call a Poison Center / Doctor.

- If on skin(or hair): Remove/ take off immediately all contaminated clothing. Rinse skin with water / shower
- If Inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Read SDS Before Use for information. For emergencies call CHEMTREC 1-800-424-9300.
- Keep out of the reach of children. Do not sell to children.
- For Industrial Use Only



Road 175 Km. 0.2 Rio Cañas  
Industrial Park Lot #35  
Caguas, PR 00725  
Tel: 787-653-4900

Fax: 787-653-4949  
email: [info@conspro.com](mailto:info@conspro.com)  
[www.bullbond.com](http://www.bullbond.com)  
[www.conspro.com](http://www.conspro.com)

