

Conspro Corp.
State Road PR-175 Km. 0.2
#35 Rio Cañas Industrial Park
Caguas, PR 00725
Tel: 787-653-4900
Fax: 787-653-4949
email: info@bull-bond.com
www.bullbond.com



Since 1967

Technical Data Sheet

MESH FABRIC T-2 MEMBRANE REINFORCING MESH FABRIC

PART 1: GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

BULL-BOND® MESH FABRIC T-2 is a white, 3 ounce stitchbonded polyester fabric used in the reinforcement of cold process roofing systems and also as a reinforcement with mastics and elastomeric.

1.2 BASIC USES:

The flexible nature of this fabric reinforcement BULL-BOND® T-2 allows for ease of application over the critical corrugations and laps found in metal roofing and conforms to smooth and semi-smooth surfaces of concrete roof decks. This product may require light brooming or dry rolling to insure good embedment and removal of any air pockets during the fabric saturation process.

PART 2: PACKAGING

- 6" x 300' Roll
- 40" x 324' Roll

PART 3: PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN. Carefully read and follow all cautions and warnings on product label and SDS. For industrial and professional use only.

PART 4: TECHNICAL DATA

4.1 PRODUCT CHARACTERISTICS:

MATERIAL PHYSICAL PROPERTIES		
PROPERTY	METHOD	BULL-BOND® MESH FABRIC T-2
Tensile Strength (1" Jaw s)	ASTM D5034	WARP 74 lbs
		WEFT 45 lbs
Elongation at Break	ASTM D5034	WARP 21.3%
		WEFT 51.3%
Elongation	ASTM D1682	61 - 63%
Ball Burst	ASTM D3787	111 lbs
Mullen Burst	ASTM D3786	176.8 lbs
Trapezoid (Tear Strength)	ASTM D1117	WARP 13.5 lbs
		WEFT 24.2 lbs
Trapezoid	ASTM D1117	16.1 lbs
Thickness	ASTM D1777	0.018
Gauge		18
CPI		18
Finished Weight		3.41 oz/square yard
Fiber		100% Polyester
Yarn		100% Polyester

Edition Date: December, 2017

©2016 Bull-Bond All rights reserved.

Check our website for the latest version of the Technical Data Sheet

Distributed by:



Road 175 Km. 0.2 Rio Cañas
Industrial Park Lot #35
Caguas, PR 00725
Tel: 787-653-4900

Fax: 787-653-4949
email: info@conspro.com
www.bullbond.com
www.conspro.com

